

YS12M SERIES

Input: 85-264VAC 50/60Hz
Output Voltage: 3V-36V DC
Rated Power: 12W max



Features


Universal AC input/ Full range
Energy efficiency level VI
Leakage Current: < 0.1mA
Extremely low leakage current
Protection: Over load/Over voltage/Short circuit
Withstand voltage : 4KV
Life Warranty: 3 years

Application

Digital equipment
Blood pressure monitor
Nebulizer



■ Dimensions and Installation




YS12M SERIES


MODEL DETAIL SPEC.		YS12-0502000	YS12-0901300	YS12-1201000	YS12-1500800	YS12-2400500	YS12-3600350
INPUT	Input Voltage range:	85-264VAC					
	Input Frequency:	50/60Hz					
	Inrush Current:	50A/230VAC					
	AC Current:	0.4A/230VAC					
	Leakage Current:	< 0.1mA/240VAC					
	Efficiency:	81.5%	84%	84%	84%	84%	84%
OUTPUT	DC Voltage:	5V	9V	12V	15V	24V	36V
	Rated Current:	2A	1.3A	1A	0.8A	0.5A	0.35A
	Rated Power:	10W	11.7W	12W	12W	12W	12W
	Voltage Tolerance:	±5.0%	±5.0%	±5.0%	±5.0%	±5.0%	±5.0%
	Ripple and Noise:	75mVp-p	90mVp-p	120mVp-p	150mVp-p	240mVp-p	300mVp-p
	Line Regulation:	±3%					
	Load Regulation:	±5%	±5%	±5%	±5%	±5%	±5%
	Setup, Rise, Hold Up time:	1000ms, 30ms/25ms 230VAC at full load					
ENVIRONMENTAL	Operating Temperature:	-20 ~ +70 (Refer to "Derating Curve")					
	Storage Temp:	-40℃ ~ 85℃					
	Storage Humidity:	10 ~ 95% RH					
	Working Humidity:	20 ~ 95% RH non-condensing					
PROTECTION	Over Load:	105% -150% rated output power					
		Protection type: Hiccup mode, recovers automatically after fault condition is removed					
	Over Voltage:	105% -130% rated output power					
		Protection type: Shut down o/p voltage, re-power on to recover					
	Short Circuit :	Shut down o/p voltage, re-power on to recover					
SAFETY & EMC	Safety Regulations:	TUV IEC/EN60601-1 approved					
	Withstand Voltage:	I/P-O/P:4KVAC I/P-FG:2KVAC O/P-FG:0.5KVAC					
	Isolation Resistance:	I/P-O/P, I/P-FG, O/P-FG:100M Ohms / 500VDC / 25℃/ 70% RH					
	EMC Emission:	Compliance to EN55032 (CISPR32), EN61000-3-2,-3					
	EMC Immunity:	EN/EN61000-4-2,3,4,5,6,8,11					
OTHER	MTBF:	500Khrs min. MIL-HDBK-217F(25℃)					
	Size:	69*27*38mm					
	Weight:	85g / pcs					
	Packaging:	100PCS/CTN					

YS12M SERIES

Deduction curve
and temperature




Static Characteristics











■ DC output plug

Standard plug: D1M

D1M			Pin Assignment	
				
			Outside	  Inside
			-V not connected to AC FG(standard) -V connected to AC FG(optional)	

YS12M SERIES

Optional DC plug: (Available in customized cable or quick adapter)

Tuning Fork Style		Type No.	A	B	C	Quick Adapter Accessory
			OD	ID	L	
 	 (Straight)	D1I	5.5	2.1	9.5	Available (Current rating: 7.5A max.)
		D1L	5.5	2.5	9.5	
		D1M	5.5	2.1	11.0	
	 (Right-angled)	D1IR	5.5	2.5	9.5	
		D1JR	5.5	2.1	11.0	
		D1LR	5.5	2.5	9.5	
		D1MR	5.5	2.5	11.0	
Barrel Style		Type No.	A	B	C	Quick Adapter Accessory
			OD	ID	L	
 	 (Straight)	D2I	5.5	2.1	9.5	None
		D2J	5.5	2.1	11.0	
		D2L	5.5	2.5	9.5	
	 (Right-angled)	D2M	5.5	2.1	11.0	
		D2IR	5.5	2.5	9.5	
		D2JR	5.5	2.1	11.0	
		D2LR	5.5	2.5	9.5	
	D2MR	5.5	2.5	11.0		
Lock Style		Type No.	A	B	C	
			OD	ID	L	
  	D2S(S761K)	5.53	2.03	12.06	None	
	D2K(761K)	5.53	2.54	12.06		
	D2C(S760 K)	5.53	2.03	9.52		
	D2D(760K)	5.53	2.54	9.52		
Center Pin Style		Type No.	A	B	C	Available (Current rating: 7.5A max.)
			OD	ID	L	
   EIAJ equivalent	D4A	5.5	3.4	11.0	1.0	
	D4B	6.5	4.4	11.0	1.4	
	D4C	7.4	5.1	11.0	0.6	
Min. Pin Style		Type No.	A	B	C	Available (Current rating: 5A max.)
			OD	ID	L	
   EIAJ equivalent	D3A	2.35	0.7	11.0		
	D3B	4.0	1.7	11.0		
	D3C	4.75	1.7	11.0		